



# ▶ CTC-1563

## Wireless Security Control Panel User Notification Panel

### Battery Operated GSM & Voice Communicating 20-Zone Control Panel CTC-1563

This professional and sophisticated battery-operated system makes a clean break from ever worrying about unexpected total power failure, and offers you the convenience of **mounting it wherever you like without the hassle of wiring to a wall outlet or phone line.**

It allows up to 6 phone numbers for voice reporting, and up to 2 SMS numbers for text messages. CTC-1563 allows you to deal with the situation and respond without any delay. Thus delivers further protection for you, your loved ones, your properties, and ensuring a peace of mind.

### Features:

- ▲ Completely wire and tangle free! Battery-operated and can be installed wherever with GSM reception, offering a flexible and easy installation
- ▲ Great solution for vacant premises, summer resorts, cruise/house boats...etc.
- ▲ Dual language available upon request
- ▲ Battery operated with life expectancy of >2 years in a typical domestic environment, optional DC power & Terminal
- ▲ A 20-zone full featured Stand-alone Wireless Control Panel
- ▲ Choice of voice reporting and/or SMS message
- ▲ 2 independent numbers for SMS reporting

- ▲ Up to 6 different phone numbers can be stored in priority order, or in 3 categories for Burglar/Panic/Technical, Fire/Gas, and Medical
- ▲ Each of the 20 zone can be individually named/edited by the user for quick recognition of designated areas
- ▲ Multiple User Codes (including Temporary and Cleaner code) ensure the ultimate security in today's life style
- ▲ 20 time-stamped event logs
- ▲ A 16 x 2 characters backlit full text LCD display
- ▲ A 16-button backlit keypad facilitate smooth user friendly operation
- ▲ 4 specific Alarm Messages of **Burglar, Fire, Panic, and Medical**, and a common Address Message can be recorded
- ▲ Call-Acknowledgement by the recipient ensures the calls are well-received
- ▲ **"Two-Way Hands-Free Voice Communication"** allows the call recipient to talk with you and listen to what's happening on your side through the built-in microphone & speaker
- ▲ Full Supervision to ensure the problem-free operation of the system (only available on 868MHZ panel)
- ▲ Capable of using power adaptor as an option

### Specifications:

- ▲ Power: Alkaline D cell x 4 or 12V 1A switching power
- ▲ Battery time: 2 years or over
- ▲ Frequency: 433 MHz / 868.35 MHz / 868.6375 MHz FM
- ▲ Range:
  - 433 MHz or 868.35 MHz: Over 200 meters in open space
  - 868.6375 MHz: Over 300 meters in open space
- ▲ Operating temperature: -10° to +45°C
- ▲ Humidity: up to 85% non-condensing
- ▲ Dimensions: 239.50 x 168 x 44 mm

Climax Technology Co., Ltd. No. 258, Hsin Hu 2nd Road, Taipei 114, Taiwan.

T 886 2 2794 0001 F 886 2 2792 6618 sales@climax.com.tw [www.climax.com.tw](http://www.climax.com.tw)