

RK110PTW



Product Description

RK110PRW is one of ROISCOCK's special designed for luxurious residential installation, which should match with RK248EW8 Wireless Receiver. Attached sole identification code, sending frequency is 433.92MHZ. It has the features as strong ability to catch signal, false & lost alarm is low, low power consumption and true temperature compensation, high technology and smart manufacture and elegant appearance, Microprocessor for digital signal processing and built-in antenna, powered by 3V lithium battery, stable performance and long service life.

RK110W can be equipped with RA93 Swivel Bracket for ceiling, wall or corner mounting.

Product Features

Coverage is 10M, with Top View Window and Creep Zone
Dual Passive Infrared Detective Technology
Microprocessor Design Improves False Alarm Immunity
True Temperature Compensation
Dual Polarity Pulse Count is Adjustable
Resist Interference of White Light
Low Power Consumption , 3V Li Battery Service Life no less than 2 years
LED Indicator when weak power and transmitting
High RFI Immunity for False Alarm Prevention (25V/M – 1GHz)
Professional Optical Pigmented Lenses
Installed on Wall, Ceiling and/or Corner Mounting
Suitable to Swivel Brackets
Convenient for Installation
Pulse Count is Selectable
Resist Fluorescent Interference
Memory and Form-C Relay
Pet immunity

Product Specification/Models

Working Voltage: 3V battery
Working Current: 40μA
Working Frequency: 433.92MHz
Alarming Time: 2.2 min
Warming-up: 2 min
RFI characteristic: 25V/m, 10 MHz ~ 1GHz
Working Temperature: 0°C ~ 55°C
Storage Temperature: -20°C ~ 60°C
Size: 128×564×40MM
Installation Height: 2.0~2.5

Packaging

Carton

Inspection

CE,CCC