

Smoke Detector SD-15 & SDA-15

Smoke Detector is a low profile and the smallest in size that utilizes the latest Optical Chamber technology to free it from potentially harmful radioactive materials. It is micro-process controlled and offers 100% Reliability, Safety and Quality you can ever get.



Features:

- Powered by Lithium battery, ensuring longer battery life
- Excellent stability with high sensitivity
- Detection method: Reflective photoelectric sensor
- Digital Signal Processing
- Randomized supervision signals for trouble-free system integrity checking
- Low Battery detection
- Diagnostic function: a Test button for self-test including optical sensor diagnosis
- Alarm silence function: 10 minutes per activation
- Built-in siren for audio alert
- Alarm Volume: 95 dB @ 1 meter
- Certification: Sensitivity **UL-217** certified
- **Specifications:**
- Power: Lithium 1/2 AA x 1
- Battery life: 8 years or over¹
- Radio frequency available:

SD-15-433:	433 MHz
SD-15-868:	868.6375 MHz Narrow FM
SDA-15:	868.35 MHz
- Range:

433 MHz	868.35 MHz:	over 200 meters in open space
	868.6375 MHz:	over 300 meters in open space
- Operating temperature: -20° to 50°C
- Humidity: up to 95% non-condensing
- Dimensions: Ø119 X 49.5 mm

* Note¹: Battery life is calculated at an average of 1 activation per day.

Technoshield Security Systems
 Website: <http://www.cyprussecurityspecialists.com>
 Email: sales@cyprussecurityspecialists.com

